



Always use appropriate Personal Protective Equipment as stated on the label or SDS.

GETTING STARTED




Step 1:

- Create a temporary blockade by utilizing appropriate signage and/or precautionary measures.
- Gather all equipment.



Step 2:

- Apply painter's tape to protect the surface that you do not want the solution to come in contact.



Step 3:

- Use a floor scraper to remove any gum or foreign objects stuck to the floor. Use a clean dust mop to remove any loose surface debris.



Step 4:

- When using an auto scrubber or Rotary machine to scrub the floor, install the proper deep scrub pad of choice.

Refer to product label for complete safety, warning and cautionary instructions.



Use SC Johnson Professional® Heavy Duty Neutral Floor Cleaner.

ROTARY MACHINE INSTRUCTIONS



Step 1:

- Dilute the SC Johnson Heavy Duty Neutral Floor Cleaner at 1:256 (½oz./gallon) in a mop & bucket with cold water, according to label instructions or follow the TruFill Dispensing instructions.



Step 2:

- To deep scrub the floor using a rotary machine, first use mop & bucket to flood the floor completely with the floor cleaning solution.



Step 3:

- Use the rotary machine to outline the perimeter of your work area.
- Box out a smaller area at the far side of the work area and swing the machine back and forth.
- Repeat this process until you've covered the entire floor.



Step 4:

- Pick up the soiled solution with a wet vac using a back and forth motion going across the work area starting from back to front.



Step 5:

- Damp mop or finse the entire area using cold water and a clean mop. Use overlapping figure 8 pattern. change water frequently to remove floor stripper residue.

COMPLETING THE TASK



Step 1:

- For best results, burnish the floor once it is completely dry with the appropriate burnishing pad. Check the pad frequently to ensure the floor is completely clean before applying finish. If pad shows excessive dirt, repeat deep scrubbing procedure to ensure floor is clean before applying finish.



Now the floor is ready to be finished using SC Johnson Professional Multi-Surface Floor Finish Plus Sealer. Refer to the floor finish application procedure.

AUTO SCRUBBER INSTRUCTIONS



Step 1:

- Fill the tank with cold water and dilute the Heavy-Duty Neutral Floor Cleaner at 1:256 (½ oz. / gallon).



Step 2:

- Outline the perimeter of the work area.
- For the first pass, in the same direction of travel, scrub the floor in overlapping passes with the squeegee up and the vacuum off - working your way from the outside edge toward the middle of your work area.



Step 3:

- For the second pass, repeat the pattern scrubbing the floor with the squeegee down and the vacuum on picking up the soiled cleaning solution.



Step 4:

- Damp mop or finse the entire area using cold water and a clean mop. Use overlapping figure 8 pattern. change water frequently to remove floor stripper residue.

COMPLETING THE TASK



Step 1:

- For best results, burnish the floor once it is completely dry with the appropriate burnishing pad. Check the pad frequently to ensure the floor is completely clean before applying finish. If pad shows excessive dirt, repeat deep scrubbing procedure to ensure floor is clean before applying finish.



Now the floor is ready to be finished using SC Johnson Professional Multi-Surface Floor Finish Plus Sealer. Refer to the floor finish application procedure.

